

## OFF ROAD – SPECIFIC REQUIREMENTS FOR OFF ROAD VEHICLES – SUPERLITE

---

**Bulletin Number: B17/002**

**Implementation Date: 3 February 2017**

### REFERENCE

CAMS Manual of Motor Sport, Off Road, Specific Requirements for Off Road Vehicles.

<https://www.cams.com.au/motor-sport/regulations/cams-manual/off-road>

### RATIONALE

The Off Road, Specific Requirements for Off Road Vehicles, 4. Superlite are amended to permit the replacement of a fuel tank.

### ACTION

The Off Road, Specific Requirements for Off Road Vehicles, 4. Superlite is amended and effective from **3 February 2017** as follows:

#### 5. SUPERLITE

...

##### 5.9 FUEL & FUEL TANK

Refer GR27 for Fuel, GR5 for Fuel Tanks and:

- ~~a) It is permitted to modify or replace a fuel tank that is positioned in the cabin for the fitment of a replacement seat. A replacement fuel tank must be fitted in the same location as the original tank, and comply with GR5.~~
- a) It is permitted to replace a fuel tank. A replacement fuel tank must be fitted in accordance with GR5 and the following:
  - (i) Be constructed of steel, stainless steel, or 5005 aluminium, a minimum 2mm thickness; and
  - (ii) Be mounted by a cradle and strap/s or, if fixed by mounting tabs, each tab shall have a mounting reinforcement of a minimum 2mm x 150cm<sup>2</sup> with large radius corners welded to the tank. Refer to Free Fuel Tank Design, Schedule N of the CAMS Manual.

**NOTE:** The use of fuel-resistant polyurethane foam baffling is highly recommended. Refer to Free Fuel Tank Design, Schedule N of the CAMS Manual.

...

END